

T3D



Camera Module Tester Series

isMedia is doing its best to develop products ranging from research development for camera test equipment's to custom-built equipment's through pre-discussion.

Feature


- CIS Package Tester
- Dual Test Zone
- Electrical Test Available (Current, Leakage)
- Compact Design(Desk-Top PC)
- Semi Auto Tester

Broaden Coverage of Function Verification

Open short test	Check sync (video signal)
Leakage test	Defect
Standby current (H/W, S/W)	Particle
Dynamic current	Optical center

Innovated Design Board Equipped

- One time sensor contact is able to verifying whole camera function test.
- 100% digital test system (Electro relay Board)
- Image sensor test available



Applicable Camera Module Type

- Wafer level package
- Chip scale package

Head Office

#1701~1706 Daeryung Techno Town 15 Cha
224-5 Gwanyang-dong, Dongan-gu,
Anyang-si, Gyeonggi-do, Korea
Tel +82-31-427-8411
Fax +82-31-463-3734
E-mail sales@ismedia.co.kr
www.ismedia.co.kr

ShenZhen Office

B-20P, CaiFuGuangChang-Bldg, CheGongmiao,
Futian-qu, ShenZhen-City,
Guangdong, China
Tel +86-755-8298-7120(CN)
+86-137-2345-9676(CN)
E-mail jakim@ismedia.co.kr
www.ismedia.co.kr

is Media

System Specification

Size / Weight	550X740X950 (WxDxH) mm / 80Kg
Utility	CDA 0.5MPa, Power 220V±5% 60Hz
Illumination	IL55 : white LED illuminator
Collimator Lens	Not available
Control Axis	1 Dual cylinder Lens adjust x.y stage
Main Processor	Intel Core 2 Duo 3.0 GHz
Memory/Hard Disk	2GB, 250GB
Monitor	20 inch
Operating System	Microsoft Windows XP, Windows 7 (32bit)
Local Bus	PCIe camera-link grabber(1ch)

H/W Specification

Interface with PC	Camera link(Base) for video USB2.0 for control
Supported Video Format	8bit to 16bit Bayer(8/10/12/14/16) 8bit or 16bit YUV4:2:2 8bit or 16bit RGB888/RGB565
Supported Control Bus	Standard I2C NON-standard I2C (16bit address,16bit data, Programmable Latency etc) SCCB
Video Transfer Rate (Supported Pixel Clock Frequency)	Up to 240MB/Sec
Supported Video Resolution	12Mp resolution camera modules are verified Now study for Higher Resolution is ongoing
Master Clock Supply	1.0M~68MHz / 0.1MHz step